

# DH-SDT4E425-8P-GB-A-PV1-SL

8+4MP 25x TiOC Network Panoramic PTZ Camera



**WizSense**

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

## System Overview

Designed with more lens than the conventional PTZ camera, the X-Spans series camera captures an expansive view, producing wide, vivid images. It has the combined power of the panoramic and detail camera in its structure and is highly cost-effective, greatly reducing the installation cost of security systems. It also leverages its two cameras to perform smart tracking, and has an independent mode that allows you to separately use each camera.

## Functions

### Starlight Technology

For challenging low-light conditions, Dahua's Starlight Ultra-low Light Technology has exceptional light sensitivity, capturing images in vivid detail, even in lighting as low as 0.005 lux. The camera uses a set of optical features to balance light throughout the scene, producing clear images in dark environments.

### Smart Codec

With advanced scene-adaptive rate control algorithm, Dahua smart codec technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

### Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

- Overview channel: Outputs 180° wide angle splicing image
- Detail channel: 1/2.8"4Megapixel CMOS
- 25x optical zoom
- Max. 25/30 fps@8M
- IR distance up to 100 m
- Auto tracking 3.0
- Smart tracking
- Perimeter protection
- Active deterrence
- Smart dual light +
- Anti-corrosion coating



### Auto Tracking

This feature controls the pan, tilt and zoom actions of the camera to automatically track an object in motion, to keep it in view of the camera. Tracking can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

### Smart Tracking

The panoramic camera links with the detail camera to track targets. When the target enters the panoramic area, the detail camera starts to monitor them and tracks their movement by rotating, zooming and focusing the PTZ camera lens. This allows the camera to produce highly detailed images with the movement of targets for security personnel.

### Smart Dual Light

Dahua Smart Dual Light technology adopts smart algorithm to detect targets. Usually, the IR illuminator is on at night; when the target appears in the monitoring area, the white light is on, and the camera records the full-color video and information of key events. That is, the camera links snapshot and video with full-color image. When the target is out of the monitoring area, the white light is off and the IR illuminator is on, which reduces light pollution efficiently.

### Protection (IP66, TVS 6000 V)

IP66, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

**Technical Specification**

**Camera**

<b>Image Sensor</b>	Overview channel: 1/2.7" CMOS; Detail channel: 1/2.8" CMOS
<b>Pixel</b>	Overview channel: 8 MP; Detail channel: 4 MP
<b>Max. Resolution</b>	Overview channel: 4096 (H) × 1860 (V); Detail channel: 2560 (H) × 1440 (V)
<b>ROM</b>	Overview channel: 4 GB; Detail channel: 4 GB
<b>RAM</b>	Overview channel: 2 GB; Detail channel: 1 GB
<b>Electronic Shutter Speed</b>	1 s–1/30,000 s
<b>Scanning System</b>	Progressive
<b>Min. Illumination</b>	Overview channel: 0.005 lux@F1.4 (Color, 30 IRE); 0.0005 lux@F1.4 (B/W, 30 IRE); 0 lux (illuminator on) Detail channel: 0.005 lux@F1.6 (Color, 30 IRE); 0.0005 lux@F1.6 (B/W, 30 IRE); 0 lux (illuminator on)
<b>Illumination Distance</b>	Overview channel: 30 m (98.43 ft) (IR); 30 m (98.43 ft) (white light); Detail channel: 100 m (328.08 ft) (IR); 50 m (131.23 ft) (white light)
<b>Illuminator On/Off Control</b>	Overview channel: Manual; Auto; Off Detail channel: Zoom Prio; Manual; Auto; Off
<b>Illuminator Number</b>	Overview channel: 2 (IR light); 2 (White light); Detail channel: 2 (IR light); 2 (Warm light)

**Lens**

<b>Focal Length</b>	Overview channel: 2.8 mm; Detail channel: 5 mm–125 mm
<b>Max. Aperture</b>	Overview channel: F1.4; Detail channel: F1.6-F3.6
<b>Field of View</b>	Overview channel: H: 180°; V: 86°; Detail channel: H: 51.9°–3.0°; V: 39.7°–2.2°; D: 63.1°–3.7°
<b>Optical Zoom</b>	Overview channel: NA; Detail channel: 25×
<b>Focus Control</b>	Auto; manual; semi-auto
<b>Close Focus Distance</b>	Overview channel: 0.6 m (1.97 ft); Detail channel: 0.1 m–0.5 m (0.33"–1.64")
<b>Iris Control</b>	Overview channel: NA; Detail channel: Auto; manual; iris prio

	Detect	Detect	Observe	Recognize	Identify
	Detail channel: W	100.0 m (328.08 ft)	40.0 m (131.23 ft)	20.0 m (65.62 ft)	10.0 m (32.81 ft)
	Detail channel: T	2500.0 m (8202.00 ft)	1000.0 m (3280.80 ft)	500.0 m (1640.40 ft)	250.0 m (820.20 ft)
*DORI (Detect, Observe, Recognize, Identify) is a standard system (EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area. The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation and commissioning manual/project design tool.					

**PTZ**

<b>Pan/Tilt Range</b>	Pan: 0° to 360° endless Tilt: –15° to +90°, auto flip 180°
-----------------------	---

<b>Manual Control Speed</b>	Pan: 0.1°/s–180°/s; Tilt: 0.1°/s–90°/s
<b>Preset Speed</b>	Pan: 0.1°/s–180°/s; Tilt: 0.1°/s–90°/s
<b>Preset</b>	300
<b>Tour</b>	8 (up to 32 presets per tour)
<b>Pattern</b>	5
<b>Scan</b>	5
<b>Power-off Memory</b>	Yes
<b>Idle Motion</b>	Preset; Pattern; Tour; Scan

**Intelligence**

<b>IVS (Perimeter Protection)</b>	Tripwire; intrusion; crossing fence detection; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; human alarm classification; linkage tracking
<b>SMD</b>	SMD 4.0

**Active Deterrence**

<b>Light Warning</b>	Red-Blue light warning; Flash duration: 5 s–30 s; Flash frequency: high, medium, low
<b>Sound Warning</b>	Offers 11 sound alarm and 10 custom sound alarms can be imported. Sound can be set from 0%–100%. Play times can be set from 1-10.

**Video**

<b>Video Compression</b>	Smart H.265+;H.265;Smart H.264+;H.264B;H.264M;H.264H;MJPEG(Sub Stream 1)
<b>Streaming Capability</b>	3 streams
<b>Resolution</b>	Overview channel: 8M (4096 × 1860); 2M (2048 × 928); 1080p (1920 × 1080); 720p (1280 × 720); 1024 × 448; D1 (704 × 576/704 × 480);VGA (640 × 480);CIF (352 × 288/352 × 240); Detail channel: 4M (2560 × 1440); 3M (2304 × 1296); 1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480);VGA (640 × 480); CIF (352 × 288/352 × 240)
<b>Video Frame Rate</b>	Overview channel: Main stream: 4096 × 1860 @ (1–25/30 fps) Sub stream 1: 1024 × 448/D1/VGA/CIF @ (1–25/30 fps) Sub stream 2: 2048 × 928/1080p/1.3M/720p @ (1–25/30 fps); Detail channel: Main stream: 4M/3M/1080p/1.3M/720p @ (1–25/30 fps) Sub stream 1: D1/VGA/CIF @ (1–25/30 fps) Sub stream 2: 1080p/1.3M/720p/ @ (1–25/30 fps)
<b>Bit Rate Control</b>	CBR/VBR
<b>Video Bit Rate</b>	Overview channel: H264: 128 kbps–16,384 kbps H265: 51 kbps–13,312 kbps; Detail channel: H264: 96 kbps–16,384 kbps H265: 38 kbps–10,240 kbps
<b>Day/Night</b>	Overview channel: Auto; Color; B/W; Electronic Detail channel: Auto; Color; B/W; Electronic
<b>BLC</b>	Yes

WDR	Overview channel: DWDR; Detail channel: 120 dB
HLC	Yes
White Balance	Overview channel: Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp Detail channel: Auto; indoor; outdoor; tracking; manual; sodium lamp; natural light; street lamp
Gain Control	Overview channel: Auto; manual; gain prio Detail channel: Auto; manual; gain prio
Noise Reduction	Overview channel: 2D NR; 3D NR Detail channel: Auto; 2D NR; 3D NR
Motion Detection	Yes
Region of Interest (RoI)	Yes
Image Stabilization	Overview channel: NA Detail channel: Electronic Image Stabilization (EIS)
Defog	Overview channel: Electronic Detail channel: Electronic
Digital Zoom	Overview channel: NA; Detail channel: 16x
Image Rotation	Overview channel: NA Detail channel: 180
S/N Ratio	Overview channel: ≥55 dB Detail channel: ≥55 dB

#### Audio

Audio Compression	PCM, G.711A, G.711Mu, G.726, MPEG2-Layer2, G.722.1, G.729
-------------------	---

#### Network

Network Port	RJ-45 (100/1,000 Base-T)
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; RTSP; UDP; SMTP; NTP; DHCP; DNS; DDNS; IPv6; 802.1x; SSL; QoS; FTP; UPnP; ICMP; SNMP; IGMP; ARP; RTCP; RTP; PPPoE; RTMP; Bonjour; NFS
Interoperability	ONVIF (Profile S & Profile G & Profile T);CGI;SDK;P2P
Streaming Method	Unicast/Multicast
User/Host	20 (total bandwidth: 64 M)
Storage	Micro SD card (512 GB); FTP/SFTP; NAS
Browser	web5.0: IE 9 and later versions; Chrome 41 and later versions; Firefox 52 and later versions; Safari 10 and later versions
Management Software	DMSS; DSS Pro
Mobile Client	iOS; Android
Management Software	DMSS; DSS Pro
Mobile Client	iOS; Android

#### Certification

Certifications	CE: EN 50130-4 EN 55032 EN 55035 EN 61000-3-3 EN IEC 61000-3-2 EN 62368-1 NEMA 4X
----------------	---

#### Port

Audio Input	1 channel (LINE IN, bare wire)
Audio Output	1 channel (LINE OUT, bare wire; built-in speaker (mutually exclusive))
Alarm Input	2 (on-off value input: 0–5 VDC)
Alarm Output	1 channel
Alarm Linkage	Capture; recording; send email; preset; tour; pattern; alarm digital output; audio; warning light
Alarm Event	Motion/tampering detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection
Alarm Event	Motion/tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection

#### Power

Power Supply	12 VDC, 3 A ± 10%; PoE (802.3at)
Power Consumption	Basic: 14 W; Max: 25 W (illuminator + heating glass + Siren and Light Active Deterrence + ICR + PTZ)
Power Adapter	Optional

#### Environment

Operating Temperature	–40 °C to +65 °C (–40 °F to +149 °F)
Operating Humidity	≤95%
Protection	IP66; TVS 6000 V lightning proof; surge protection; voltage transient protection

#### Structure

Product Dimensions	194.2 mm × 160 mm × 311 mm (7.65" × 6.30" × 12.24") (L × W × H)
Net Weight	3.1 kg (6.83 lb)
Gross Weight	4.6 kg (10.14 lb)

#### Ordering Information

Type	Model	Description
Network PTZ Camera	DH-SDT4E425-8P-GB-A-PV1-SL	8+4MP 25x TiOC Network Panoramic PTZ Camera
	PFB305WA	Wall Mount Bracket
Accessories	PFA114A	Anti-corrosion Mount Adapter
	PFB300CA	Anti-corrosion Wall Mount Bracket
	PFA151A	Anti-corrosion Corner Mount Bracket
	PFA155A	Anti-corrosion Pole mount bracket
	PFA126A	Anti-corrosion Junction Box

**Accessories**

Included:



PFB305WA  
Wall Mount Bracket

Optional:



PFA126A  
Anti-corrosion  
Junction Box



PFA151A  
Anti-corrosion Corner  
Mount Bracket



PFA155A  
Anti-corrosion  
Pole mount  
bracket



PFB300CA  
Anti-corrosion Wall Mount  
Bracket

Wall Mount	Ceiling Mount 1	Pole Mount (Vertical)
PFB305WA+PFA126A	PFA114A+DH-PFB300CA	PFB305WA+DH-PFA155A
Pole Mount (Horizontal)	Corner Mount	
PFA114A+DH-PFB300CA+DH-PFA155A	PFB305WA+DH-PFA151A	

**Dimensions (mm[inch])**

